## 1001 RS-1 One-Family Residential

#### (1) Intent

This zone provides exclusively for the development of low *density* single *family lots* with a minimum *lot size* of  $650 \text{ m}^2$ , with limited appropriate *accessory uses*.

## (2) Permitted Uses

*Principal uses*, limited to:

(a) One-family residential

*Accessory uses,* limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Accessory residential
- (d) Accessory home occupation, as limited under Section 508(3)

### (3) Conditions of Use

Not applicable in this zone.

#### (4) Lot Size

- (a) A one-family residential use is not permitted on a lot having an area less than:
  - (i) 650 m<sup>2</sup>; or
  - (ii) 555 m<sup>2</sup>, where the *lot* being subdivided has an area between 1,110 m<sup>2</sup> and 1951 m<sup>2</sup> and was in existence prior to 1996 02 19.
- (b) The minimum lot width is 13.5 metres;
- (c) The minimum lot depth is 22.7 metres;
- (d) The maximum *lot size* for a public park is 0.8 hectares.

## 1001 RS-1 One-Family Residential

## (5) Density

- (a) The maximum *density* shall be 18 units per hectare;
- (b) When calculating units per hectare, *secondary suite dwelling units* are excluded from the calculation.

### (6) Lot Coverage

All buildings and structures together must not exceed a lot coverage of 45%.

## (7) Buildings Per Lot

No more than one *principal building* is permitted per *lot*.

## (8) Setbacks

(a) Buildings and structures for the following uses must meet the siting distance from other buildings and structures where applicable and be sited no closer than the corresponding setbacks from the lot lines set out below:

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
One-family residential, and-public parks	7.6	7.6	1.8	3.8
Accessory residential and accessory off- street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	7.6	7.6	1.8	3.8
Detached accessory residential and accessory off-street parking buildings and structures where sited 1.6 metres or more from a building for residential use	7.6	1.2	1.2	3.8

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater.
- (c) The above setback may increase under Sections 518, 519 and 523 or decrease under Section 514.

## 1001 RS-1 One-Family Residential

## (9) Location of Uses

Secondary suite use, see Section 508(2).

#### (10) Height

- (a) Buildings and structures for one-family residential use must not exceed a height of:
  - (i) 7.3 metres; or
  - (ii) 11.0 metres for *buildings* and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.


## (11) Building Size

- (a) The maximum volume occupied by the *principal building* on a *lot* shall be determined by the simultaneous consideration on each face of the *building* of both the *perimeter wall height* and the *perimeter wall area* as specified below:
  - (i) The average *perimeter wall height* of each *outermost building face*, when considering the slope of the *lot*, will be determined by the following:

(i.i)	0.00 to 1.00 % slope at each property line	6.1 metres
	1.01 to 5.00 % slope at each property line	6.4 metres
	5.01 to 10.00 % slope at each property line	6.7 metres
	10.01 to 15.00 % slope at each property line	7.0 metres
	15.01 % slope or greater	7.3 metres

- (i.ii) Parts of the building wall length may exceed the maximum perimeter wall height, but must never exceed a maximum wall height of 8.4 metres.
- (ii) Those parts of the *building* that extend beyond a plane formed by lines projecting inward at an angle of 45 degrees from the vertical at the respective permitted average *perimeter wall heights* as measured from grade along the lines of the *outermost building faces*, will be considered in the determination of average *perimeter wall height*. Gable ends, dormers and those parts of the building *wall* identified under sub-section (11)(a)(i)(i.i) will not be included in the determination of average *perimeter wall height*.

### 1001 RS-1 One-Family Residential



(iii) The *perimeter wall area* of each *outermost building face*, when considering the slope of the *lot*, will be determined by the following:

(iii.i)	0.00 to 1.00 % slope at each property line	93 sq. metres
	1.01 to 5.00 % slope at each property line	97 sq. metres
	5.01 to 10.00 % slope at each property line	102 sq. metres
	10.01 to 15.00 % slope at each property	107 sq. metres
	line	-
	15.01 % slope or greater	110 sq. metres

- (iii.ii) The area of gable ends and dormers above the second floor that face the side property line opposite another building site must be counted in the calculation of *perimeter wall area*, except if the face of the gable end or dormer is set back at least 2.4 metres from the building face of the floor below.
- (iv) Sub-section (11)(a) does not apply to properties located in the highlighted areas shown on Schedules 'B', 'C', and 'D' to this Bylaw.
- (b) The maximum length of any wall of a detached building or structure for an accessory residential use and an accessory off-street parking use is 9.2 metres.

### (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

### (13) Other Regulations

The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.

## 1002 RS-2 One-Family Suburban Residential

#### (1) Intent

This zone provides for the development of low *density* single *family* housing on large acreage *lots* of minimum 4000 m<sup>2</sup> which may or may not have water services.

Agricultural uses are also permitted.

#### (2) Permitted Uses

*Principal uses*, limited to:

- (a) One-family residential
- (b) Agricultural, as limited under Sub-section (3)(a)

Accessory uses, limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Accessory residential
- (d) Accessory home occupation, as limited under Section 508(3)
- (e) Accessory produce sales, as limited under Sub-section (11)(a)

### (3) Conditions of Use

- (a) An agricultural use:
  - (i) must not have more than one horse, cow, sheep or goat per 1,000 square metres of *lot area*; and
  - (ii) not including mushroom growing, the keeping for *commercial* purposes of swine, poultry or fur-bearing animals and the keeping of dogs, except as permitted as an *accessory residential use*; and
  - (iii) does not include a medical cannabis grow operation.

### 1002 RS-2 One-Family Suburban Residential

## (4) Lot Size

The following *uses* are not permitted on *lots* having an area less than the corresponding areas below:

<u>Use</u>	<u>Minimum Lot Area (m²)</u>
Agricultural	4,000
One-family residential	4,000
Accessory produce sales	4,000

- (a) The minimum lot depth is 22.7 metres.
- (b) The maximum *lot size* for a public park is 0.8 hectares.

## (5) Density

- (a) The maximum density shall be 2.5 units per hectare.
- (b) When calculating units per hectare, *secondary suite dwelling units* are excluded from the calculation.

## (6) Lot Coverage

- (a) All buildings and structures together must not exceed a lot coverage of 45%.
- (b) All buildings and structures for agricultural use must not exceed a lot coverage of 20%.

## (7) Buildings Per Lot

No more than one *principal building* for *residential use* is permitted per *lot*.

#### (8) Setbacks

(a) Buildings and structures for the following uses must meet the siting distance from other buildings and structures where applicable and be sited no closer than the corresponding setbacks from lot lines, bodies of water and other uses set out below:

# 1002 RS-2 One-Family Suburban Residential

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)	Wells or Streams (metres)	Distance from One- Family Residential Use (metres)
One-family residential and public parks	7.6	7.6	1.8	3.8	See Sections 519 and 523	
Agricultural	30	15	15	30	30	15
Accessory residential and accessory off-street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	7.6	7.6	1.8	3.8	See Sections 519 and 523	Attached or less than 1.6
Detached accessory residential and accessory off-street parking buildings and structures where sited 1.6 metres or more from a building for residential use	7.6	1.2	1.2	3.8	See Sections 519 and 523	1.6 or more

- (b) the siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater.
- (c) The above setbacks may increase under Sections 518, 519 and 523 or decrease under Section 514.

## (9) Location of Uses

Secondary suite use, see Section 508(2).

## 1002 RS-2 One-Family Suburban Residential

## (10) Height

- (a) Buildings and structures for one-family residential use must not exceed a height of:
  - (i) 7.3 metres, or
  - (ii) 11.0 metres for buildings and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Detached buildings and *structures* for *accessory residential* or *accessory off-street* parking must not exceed a height, measured from *finished grade*, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.

### (11) Building Size

The maximum total floor area of buildings and structures for accessory produce sales use is  $12 \text{ m}^2$ .

## (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

### (13) Other Regulations

The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.

## 1003 RS-3 One-Family Residential

#### (1) Intent

This zone provides for the development of low *density* single *family lots* with a minimum *lot size* of 555  $m^2$ , with limited appropriate *accessory uses*.

### (2) Permitted Uses

*Principal uses*, limited to:

(a) One-family residential

*Accessory uses*, limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Accessory residential
- (d) Accessory home occupation, as limited under Section 508(3)

### (3) Conditions of Use

Not applicable in this zone.

## (4) Lot Size

- (a) A one-family residential use is not permitted on a lot having an area less than 555 m<sup>2</sup>;
- (b) The minimum *lot width* is 13.5 metres;
- (c) The minimum *lot* depth is 22.7 metres;
- (d) The maximum *lot size* for a public park is 0.8 hectares.

### (5) Density

- (a) The maximum *density* shall be 18 units per hectare.
- (b) When calculating units per hectare, *secondary suite dwelling units* are excluded from the calculation.

## 1003 RS-3 One-Family Residential

## (6) Lot Coverage

All buildings and structures together must not exceed a lot coverage of 45%.

## (7) Buildings Per Lot

No more than one principal building is permitted per lot.

## (8) Setbacks

(a) Buildings and structures for the following uses must meet the siting distance from other buildings and structures where applicable and be sited no closer than the corresponding setbacks from the lot lines set out below:

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
One-family residential and public parks	7.6	7.6	1.8	3.8
Accessory residential and accessory off- street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	7.6	7.6	1.8	3.8
Detached accessory residential and accessory off-street parking buildings and structures where sited 1.6 metres or more from a building for residential use	7.6	1.2	1.2	3.8

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater, except as specifically excluded.
- (c) The above setbacks may increase under Sections 518, 519 and 523 or decrease under Section 514.

### (9) Location of Uses

Secondary suite use, see Section 508(2).

## 1003 RS-3 One-Family Residential

#### (10) Height

- (a) Buildings and structures for one-family residential use must not exceed a height of:
  - (i) 7.3 metres; or
  - (ii) 11.0 metres for *buildings* and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.


## (11) Building Size

- (a) The maximum volume occupied by the *principal building* on a *lot* shall be determined by the simultaneous consideration on each face of the *building* of both the *perimeter wall height* and the *perimeter wall area* as specified below:
  - (i) The average *perimeter wall height* of each *outermost building face*, when considering the slope of the *lot*, will be determined by the following:

(i.i)	0.00 to 1.00 % slope at each property line	6.1 metres
	1.01 to 5.00 % slope at each property line	6.4 metres
	5.01 to 10.00 % slope at each property line	6.7 metres
	10.01 to 15.00 % slope at each property line	7.0 metres
	15.01 % slope or greater	7.3 metres

- (i.ii) Parts of the building *wall* length may exceed the maximum *perimeter wall height*, but must never exceed a maximum *wall* height of 8.4 metres.
- (ii) Those parts of the *building* that extend beyond a plane formed by lines projecting inward at an angle of 45 degrees from the vertical at the respective permitted average *perimeter wall heights* as measured from grade along the lines of the *outermost building faces*, will be considered in the determination of average *perimeter wall height*. Gable ends, dormers and those parts of the building *wall* identified under sub-section (11)(a)(i)(i.i) will not be included in the determination of average *perimeter wall height*.

### 1003 RS-3 One-Family Residential



(iii) The *perimeter wall area* of each *outermost building face*, when considering the slope of the *lot*, will be determined by the following:

	3	
(iii.i)	0.00 to 1.00 % slope at each property line	93 sq. metres
	1.01 to 5.00 % slope at each property line	97 sq. metres
	5.01 to 10.00 % slope at each property line	102 sq. metres
	10.01 to 15.00 % slope at each property line	107 sq. metres
	15.01 % slope or greater	110 sq. metres

- (iii.ii) The area of gable ends and dormers above the second floor that face the side property line opposite another *building* site must be counted in the calculation of *perimeter wall area*, except if the face of the gable end or dormer is set back at least 2.4 metres from the *building* face of the floor below.
- (iv) Sub-section (11)(a) does not apply to properties located in the highlighted areas shown on Schedules 'B', 'C', and 'D' to this Bylaw.
- (b) The maximum length of any wall of a detached building or structure for an accessory residential use and an accessory off-street parking use is 9.2 metres.

#### (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

### (13) Other Regulations

The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.

## 1004 RS-4 One-Family Compact Residential

#### (1) Intent

This zone provides for the development of low *density* single *family lots* with a minimum *lot size* of 375 m<sup>2</sup>, with limited appropriate accessory facilities.

## (2) Permitted Uses

*Principal uses*, limited to:

(a) One-family residential

*Accessory uses*, limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Accessory residential
- (d) Accessory home occupation, as limited under Section 508(3)

### (3) Conditions of Use

Not applicable in this zone.

## (4) Lot Size

- (a) A one-family residential use is not permitted on a lot having an area less than 375 m<sup>2</sup>;
- (b) The minimum *lot width* is 12.5 metres
- (c) The minimum lot depth is 22.7 metres;
- (d) The maximum *lot size* for a public park is 0.8 hectares.

### (5) Density

- (a) The maximum *density* shall be 27 units per hectare.
- (b) When calculating units per hectare, *secondary suite dwelling units* are excluded from the calculation.

## 1004 RS-4 One-Family Compact Residential

## (6) Lot Coverage

All buildings and structures together must not exceed a lot coverage of 45%.

## (7) Buildings Per Lot

No more than one *principal building* is permitted per *lot*.

### (8) Setbacks

(a) Buildings and structures for the following uses must meet the siting distance from other buildings and structures where applicable and be sited no closer than the corresponding setbacks from the lot lines set out below:

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Line (for portion of Building one storey or less) (metres)	Interior Side Lot Line (for portion of Building more than one storey) (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
One-family residential and public parks	6	6	1.25	1.75		3
Accessory residential and accessory off-street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	6	6	1.25	1.75		3
Detached accessory residential and accessory off-street parking buildings and structures where sited 1.6 metres or more from a building for residential use	7.6	1.2			1.2	3.8

## 1004 RS-4 One-Family Compact Residential

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater.
- (c) Despite Sub-section (8)(a), a reduced front setback is permitted, as long as the average setback of the front faces of the *buildings* and *structures* on the *lot* is not less than 6 metres from the *front lot line* and no part of any *building* or *structure* is less than 2 metres from a *front lot line*. This reduction is not permitted on any *lot* which has an *exterior side lot line*.
- (d) The above setbacks may increase under Sections 518, 519 and 523 or decrease under Section 514.

#### (9) Location of Uses

Secondary suite use, see Section 508(2).

## (10) Height

- (a) Buildings and structures for one-family residential use must not exceed a height of:
  - (i) 7.3 metres, or
  - (ii) 9.0 metres for *buildings* and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.

### (11) Building Size

The maximum length of any wall of a detached building or structure for an accessory residential use and an accessory off-street parking use is 9.2 metres.

#### (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

#### (13) Other Regulations

The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.

This page is intentionally left blank

## 1005 RS-5 One-Family Compact (Strata Lot) Residential

#### (1) Intent

This zone provides for low *density* bare land strata single *family lots* with a minimum *lot size* of 375 m<sup>2</sup>, with limited appropriate *accessory uses*.

## (2) Permitted Uses

*Principal uses*, limited to:

(a) One-family residential

*Accessory uses,* limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Accessory residential
- (d) Accessory home occupation, as limited under Section 508(3)

### (3) Conditions of Use

Not applicable in this zone.

## (4) Lot Size

- (a) A one-family residential use is not permitted on a strata lot having an area less than 375 m<sup>2</sup>;
- (b) The minimum *lot width* is 12.5 metres;
- (c) The minimum lot depth is 22.7 metres;
- (d) The maximum *lot size* for a public park is 0.8 hectares.

### (5) Density

- (a) The maximum *density* shall be 27 units per hectare.
- (b) When calculating units per hectare, *secondary suite dwelling units* are excluded from the calculation.

## 1005 RS-5 One-Family Compact (Strata Lot) Residential

## (6) Lot Coverage

All buildings and structures together must not exceed a lot coverage of 45%.

## (7) Buildings Per Lot

No more than one *principal building* is permitted per *strata lot*.

### (8) Setbacks

(a) Buildings and structures for the following uses must meet the siting distance from other buildings and structures where applicable and be sited no closer than the corresponding setbacks from the lot lines set out below:

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Line (for portion of Building one storey or less) (metres)	Interior Side Lot Line (for portion of Building more than one storey) (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
One-family residential and public parks	6	6	1.25	1.75		3
Accessory residential and accessory off-street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	6	6	1.25	1.75		3
Detached accessory residential and accessory off-street parking buildings and structures where sited 1.6 metres or more from a building for residential use	7.6	1.2			1.2	3.8

## 1005 RS-5 One-Family Compact (Strata Lot) Residential

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater, except as specifically excluded.
- (c) Despite Sub-section (8)(a), a reduced front setback is permitted, as long as the average setback of the front faces of the *buildings* and *structures* on the *lot* is not less than 6 metres from the *front lot line* and no part of any *building* or *structure* is less than 2 metres from a *front lot line*. This reduction is not permitted on any *lot* which has an *exterior side lot line*.
- (d) The above setbacks may increase under Sections 518, 519 and 523 or decrease under Section 514.

## (9) Location of Uses

Secondary suite use, see Section 508(2).

### (10) Height

- (a) Buildings and structures for one-family residential use must not exceed a height of:
  - (i) 7.3 metres, or
  - (ii) 9.0 metres for *buildings* and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.

#### (11) Building Size

The maximum length of any wall of a detached building or structure for an accessory residential use and an accessory off-street parking use is 9.2 metres.

## (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

#### (13) Other Regulations

Not applicable in this zone.

This page is intentionally left blank

## 1006 RS-6 One-Family (Strata Lot) Residential

#### (1) Intent

This zone provides for low *density* bare land strata single *family lots* with a minimum *lot size* of 555 m<sup>2</sup>, with limited appropriate *accessory uses*.

## (2) Permitted Uses

*Principal uses*, limited to:

(a) One-family residential

*Accessory uses*, limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Accessory residential
- (d) Accessory home occupation, as limited under Section 508(3)

### (3) Conditions of Use

Not applicable in this zone.

## (4) Lot Size

- (a) A *one-family residential use* is not permitted on a *strata lot* having an area less than 555 m<sup>2</sup>;
- (b) The minimum lot depth is 22.7 metres;
- (c) The maximum *lot size* for a public park is 0.8 hectares.

## (5) Density

- (a) The maximum *density* shall be 18 units per hectare.
- (b) When calculating units per hectare, *secondary suite dwelling units* are excluded from the calculation.

## 1006 RS-6 One-Family (Strata Lot) Residential

## (6) Lot Coverage

All buildings and structures together must not exceed a lot coverage of 45%.

## (7) Buildings Per Lot

No more than one *principal building* is permitted per *strata lot*.

## (8) Setbacks

(a) Buildings and structures for the following uses must meet the siting distance from other buildings and structures where applicable and be sited no closer than the corresponding setbacks from the lot lines set out below:

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
One-family residential and public parks	7.6	7.6	1.8	3.8
Accessory residential and accessory off- street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	7.6	7.6	1.8	3.8
Detached accessory residential and accessory off-street parking buildings and structures where sited 1.6 metres or more from a building for residential use	7.6	1.2	1.2	3.8

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater, except as specifically excluded.
- (c) The above setbacks may increase under Sections 518, 519 and 523 or decrease under Section 514.

#### (9) Location of Uses

Secondary suite use, see Section 508(2).

#### 1006 RS-6 One-Family (Strata Lot) Residential

## (10) Height

- (a) Buildings and structures for one-family residential use must not exceed a height of:
  - (i) 7.3 metres, or
  - (ii) 11.0 metres for *buildings* and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.


## (11) Building Size

- (a) The maximum volume occupied by the *principal building* on a *lot* shall be determined by the simultaneous consideration on each face of the *building* of both the *perimeter wall height* and the *perimeter wall area* as specified below:
  - (i) The average *perimeter wall height* of each *outermost building face*, when considering the slope of the *lot*, will be determined by the following:

(i.i)	0.00 to 1.00 % slope at each property line	6.1 metres
	1.01 to 5.00 % slope at each property line	6.4 metres
	5.01 to 10.00 % slope at each property line	6.7 metres
	10.01 to 15.00 % slope at each property line	7.0 metres
	15.01 % slope or greater	7.3 metres

- (i.ii) Parts of the building *wall* length may exceed the maximum *perimeter wall height*, but must never exceed a maximum *wall* height of 8.4 metres.
- (ii) Those parts of the *building* that extend beyond a plane formed by lines projecting inward at an angle of 45 degrees from the vertical at the respective permitted average *perimeter wall heights* as measured from grade along the lines of the *outermost building faces*, will be considered in the determination of average *perimeter wall height*. Gable ends, dormers and those parts of the building *wall* identified under sub-section (11)(a)(i)(i.i) will not be included in the determination of average *perimeter wall height*.

### 1006 RS-6 One-Family (Strata Lot) Residential



(iii) The *perimeter wall area* of each *outermost building face*, when considering the slope of the *lot*, will be determined by the following:

(iii.i)	0.00 to 1.00 % slope at each property line	93 sq. metres	
	1.01 to 5.00 % slope at each property line	97 sq. metres	
	5.01 to 10.00 % slope at each property line	102 sq. metres	
	10.01 to 15.00 % slope at each property	107 sq. metres	
	line	-	
	15.01 % slope or greater	110 sq. metres	

- (iii.ii) The area of gable ends and dormers above the second floor that face the side property line opposite another *building* site must be counted in the calculation of *perimeter wall* area, except if the face of the gable end or dormer is set back at least 2.4 metres from the *building* face of the floor below.
- (iv) Sub-section (11)(a) does not apply to properties located in the highlighted areas shown on Schedules 'B', 'C', and 'D' to this Bylaw.
- (b) The maximum length of any wall of a detached building or structure for an accessory residential use and an accessory off-street parking use is 9.2 metres.

## (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

#### (13) Other Regulations

The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.

## 1007 RS-7 Small Village Single Family Residential

#### (1) Intent

This zone provides for the development of single family lots with a minimum *lot size* of 340 m<sup>2</sup>, with limited appropriate *accessory uses*.

### (2) Permitted Uses

*Principal uses*, limited to:

- (a) One-family residential
- (b) Duplex residential, as limited under Sub-section (3)(a)

*Accessory uses,* limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Carriage House, as limited under Sub-sections (3)(b) (8)(f) and (9)(g)
- (d) Accessory residential, as limited under Sub-section (9)(a)
- (e) Accessory home occupation, as limited under Section 508(3)

### (3) Conditions of Use

- (a) A duplex residential use is permitted only on a lot with an exterior lot corner.
- (b) A carriage house is only permitted where it complies with all of the following:
  - (i) is in conjunction with a one-family residential use;
  - (ii) only one secondary suite, or carriage house, is permitted per lot; and
  - (iii) only at the following locations:

Portions of Lot 1 Section 7 Township 40 New Westminster District Plan76704; PID 009-456-031 (3434 Roxton Avenue);

Portions of Lot 2 Section 7 Township 40 New Westminster District Plan76704; PID 009-456-066 (3438 Roxton Avenue); and

Portions of Lot H Section 7 Township 40 New Westminster District Plan17587; PID 004-121-198 (3444 Roxton Avenue);

As shown in bold on Schedule "M" to this Bylaw; and

(iv) a *carriage house* is not subject to *subdivision* under the provisions of either the Land Title Act or the Strata Property Act.

## (4) Lot Size

- (a) A one-family residential use:
  - (i) is not permitted on a *lot* having an area less than 340 m<sup>2</sup>;
  - (ii) must have a minimum *lot width* of 10 metres, except that for a *lot* having an attached *accessory off-street parking structure* accessed from a fronting *street* the minimum *lot width* is 12.8 metres; and
  - (iii) notwithstanding Sub-section (4)(a)(ii), the minimum *lot width* for a *lot* with an *exterior lot corner* is 13.1 metres.
- (b) A duplex residential use:
  - (i) is not permitted on a *lot* having an area less than 550 m<sup>2</sup>; and
  - (ii) must have a minimum lot width of 16.3 metres.

## (5) Density

- (a) The maximum density shall be 29 principal buildings per hectare.
- (b) The maximum floor area of the principal building on each lot is 340 m<sup>2</sup>, except that for the principal building containing a duplex residential use the maximum floor area of the principal building is 420 m<sup>2</sup>, with a further exception that the floor area of the principal building in both cases may be increased by up to 40 m<sup>2</sup> for an attached accessory off-street parking use.
- (c) The maximum *floor area* of a *carriage house use* on a *lot* is 50 m<sup>2</sup>, except that, the *floor area* may be increased by up to 4.6 m<sup>2</sup> for the purpose of storage, located at grade, and with no access from the interior of said *building*.
- (d) When calculating units per hectare, *secondary suite dwelling units* are excluded from the calculation.

## (6) Lot Coverage

All buildings and structures together must not exceed a lot coverage of 45%.

#### (7) Buildings Per Lot

One *principal building* and where permitted one *accessory residential building* that contains a *carriage house use* is permitted per *lot*.

#### (8) Setbacks

(a) Buildings and structures for the following uses must meet the siting distance from other buildings and structures where applicable and be sited no closer than the corresponding setbacks from the lot lines set out below:

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
One-family residential; Duplex residential; and public parks	4.0	6.2	1.2	3.0
Carriage house	Not applicable. See Sub- sections (8)(e), (8)(f) and (9)(f)	1.2	1.2	3.0
Accessory residential buildings and structures attached to or sited less than 1.6 metres from a building for residential use	4.0	6.2	1.2	3.0
Accessory off-street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	6.0 See Sub-section (9)(b)	6.2	1.2	3.0
Detached accessory residential and accessory off-street parking buildings and structures where sited 1.6 metres or more from a building for residential use	Not applicable. See Sub- sections (8)(e), (9)(a) and (9)(b)	1.2	0.9	3.0

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater, except as specifically excluded.
- (c) The above setbacks may increase under Sections 518, 519 and 523 or decrease under Section 514.
- (d) Notwithstanding Section 514(2), covered porches are permitted to project by up to 1.7 metres into the front yard setback provided that:

- (i) the porch shall have a usable floor space with dimensions that are no less than 1.5 metres by 3.0 metres;
- (ii) the porch shall be unenclosed and protected by guard rails that comply with the British Columbia Building Code;
- (iii) the porch is located at the basement or first storey; and
- (iv) the porch is limited to a single *storey* in height, and its height does not exceed 4.0 metres, measured from the porch floor to the underside of the porch ceiling.
- (e) A minimum separation distance of 6.0 metres between the outermost projection of the principal building and any detached accessory buildings or accessory off-street parking structures.
- (f) A minimum separation distance of 8.0 metres between the outermost projection of the rear face of the *principal building*, excluding sundecks or stairs and a *building* or *structure* that contains a *carriage house use*.
- (g) Section 514(1) of the Zoning Bylaw may be applied only within one interior side setback area of the lot, however, no unglazed projection other than chimneys may extend beyond a single *storey* in height; and with the exception of eaves, Section 514(2) does not apply to the *interior side lot line* setback requirements.

## (9) Location of Uses

- (a) All detached accessory buildings shall be located in the rear yard.
- (b) Where a lane is provided all accessory off-street parking buildings or structures shall be located in the rear yard and access to accessory off-street parking spaces shall be from the lane.
- (c) The first storey of the principal building (including covered porches meeting the requirements under Sub-section (8)(d) and attached to the main front door entrance) must be:
  - (i) a minimum of 35% of the width of the buildings and structures facing the front lot line;
  - (ii) located at least 1.0 metre in front of any garage door(s); and
  - (iii) notwithstanding sub-section (9)(c)(i), for a lot where the width of the lot at the *front lot line* is less than the minimum *lot width* as regulated under sub-sections (4)(a) and (4)(b), Sub-section (9)(c)(i) will not apply.
- (d) No more than two *accessory off-street parking* spaces may be contained within the *principal building*.

- (e) Accessory off-street parking spaces are not permitted within an exterior side lot line setback, access driveway or front yard, except for unenclosed parking for a secondary suite, which must not be within 6 metres of the exterior lot corner.
- (f) A carriage house use must be located in the rear yard and is only permitted where a lane is provided.

#### (10) Height

- (a) Buildings and structures for one-family residential or duplex residential uses must not exceed a height of:
  - (i) 7.3 metres, or
  - (ii) 11.0 metres for *buildings* and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Buildings and structures for a carriage house use must not exceed a height of:
  - (i) 5.5 metres; or
  - (ii) 7.0 metres, for *buildings* and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (c) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.

#### (11) Building Size

- (a) The exterior wall of the uppermost storey of the principal building must be set back from the main floor front exterior wall by a minimum of 0.6 metres.
  - (i) if the *storey* immediately below the uppermost *storey* is the first *storey*, which includes a front covered porch, the floor space of the front covered porch, measured to the outside edge of posts supporting the covered porch roof is added to the first *storey floor area* for this calculation;
  - (ii) if the *storey* immediately below the uppermost *storey* is the first *storey*, which includes an enclosed garage, the floor space of the enclosed garage is added to the first *storey floor area* for this calculation.

- (b) Sub-section (11)(a) does not apply:
  - (i) if in the case of a corner *lot*, there is a maximum of one *storey* of the *principal* building facing the narrowest *lot* line along the street; and
  - (ii) in all other cases, if there is a maximum of one *storey* of the *principal building* facing the street.
- (c) The maximum length of any wall of a building or structure for an accessory residential use and an accessory off-street parking use, including a carriage house use is:
  - (i) 9.2 metres where the principal use is one-family residential; and
  - (ii) 12.4 metres where the *principal use* is *duplex residential*.

## (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

#### (13) Other Regulations

- (a) Landscaping requirements for development in Northeast Coquitlam, under Part 5.
- (b) Provide a private outdoor space defined by *fences*, railings or landscaping, having an area not less than 4.0 m<sup>2</sup>, that has direct access to habitable space, specific for and where a *carriage house use* is located on a *lot*.
- (c) The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.

## 1008 RS-8 Large Village Single Family Residential

#### (1) Intent

This zone provides for the development of single family lots with a minimum *lot size* of 400 m<sup>2</sup>, with limited appropriate *accessory uses*.

## (2) Permitted Uses

*Principal uses*, limited to:

(a) One-family residential

*Accessory uses*, limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Accessory residential, as limited under Sub-section (9)(a)
- (d) Accessory home occupation, as limited under Section 508(3)

### (3) Conditions of Use

Not applicable in this zone.

#### (4) Lot Size

- (a) A one-family residential use is not permitted on a lot having an area less than 400 m<sup>2</sup>.
- (b) The minimum lot width is 12 metres, except that for a lot having an attached accessory parking structure accessed from a fronting street, the minimum lot width is 12.8 metres.
- (c) Notwithstanding Sub-section (4)(b), the minimum *lot width* for a *lot* with an *exterior lot corner* is 13.1 metres.

## (5) Density

- (a) The maximum *density* shall be 25 *principal buildings* per hectare.
- (b) The maximum floor area of the principal building on each lot is 365 m<sup>2</sup>, except that the floor area may be increased by up to 40 m<sup>2</sup> for an attached accessory off-street parking use.

## (6) Lot Coverage

All buildings and structures together must not exceed a lot coverage of 45%.

## (7) Buildings Per Lot

No more than one *principal building* is permitted per *lot*.

## (8) Setbacks

(a) Buildings and structures for the following uses must meet the siting distance from other buildings and structures where applicable and be sited no closer than the corresponding setbacks from the lot lines set out below:

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
One-family residential; and public parks	4.0	6.2	1.2	3.0
Accessory residential buildings and structures attached to or sited less than 1.6 metres from a building for residential use	4.0	6.2	1.2	3.0
Accessory off-street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	6.0 See Sub-sec. (9)(b)	6.2	1.2	3.0
Detached accessory residential and accessory off-street parking buildings and structures where sited at 1.6 metres or more from a building for residential use	Not applicable. See Sub-sections (8)(e), (9)(a) and (9)(b)	1.2	1.2	3.0

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater.
- (c) The above setbacks may increase under Sections 518, 519 and 523 or decrease under Section 514.
- (d) Notwithstanding Section 514(2), covered porches are permitted to project by up to 1.7 metres into the front yard setback provided that:
  - (i) the porch shall have a usable floor space with dimensions that are no less than 1.5 metres by 3.0 metres;
  - (ii) the porch shall be unenclosed and protected by guard rails that comply with the British Columbia Building Code;
  - (iii) the porch is located at the basement or first storey; and
  - (iv) the porch is limited to a single *storey* in height, and its height does not exceed 4.0 metres, measured from the porch floor to the underside of the porch ceiling.
- (e) A minimum separation distance of 6.0 metres shall be maintained between the outermost projection of the rear face of the *principal building* and any detached *accessory buildings* or *accessory off-street parking structures*.
- (f) Section 514(1) of the Zoning Bylaw may be applied only within one interior side yard setback area, however, no unglazed projection other than chimneys may extend beyond a single *storey* in *height*; and with the exception of eaves, Section 514(2) does not apply to the *interior side lot line* setback requirements.

#### (9) Location of Uses

- (a) All detached accessory buildings shall be located in the rear yard.
- (b) Where a lane is provided all accessory off-street parking structures shall be located in the rear yard and access to accessory off-street parking spaces shall be from the lane.
- (c) The first *storey* of the *principal building* (including covered porches meeting the requirements under Sub-section (8)(d) and attached to the main front door entrance) must be:
  - (i) a minimum of 35% of the width of the buildings and structures facing the front lot line;
  - (ii) located at least 1.0 metre in front of any garage door(s); and
  - (iii) notwithstanding Sub-section (9)(c)(i), for a *lot* where the width of the *lot* at the *front lot line* is less than the minimum *lot width* as regulated under Sub-sections (4)(b) and (4)(c), Sub-section (9)(c)(i) will not apply.
- (d) No more than two *accessory off-street parking* spaces may be contained within the *principal building*.

(e) Accessory off-street parking uses are not permitted within an exterior side lot line setback, except for unenclosed parking for a secondary suite, which must not be within 6 metres of the exterior lot corner.

## (10) Height

- (a) Buildings and structures for one-family residential use must not exceed a height of:
  - (i) 7.3 metres, or
  - (ii) 11.0 metres for buildings and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.

## (11) Building Size

- (a) The exterior wall of the uppermost storey of the principal building must be set back from the main floor front exterior wall by a minimum of 0.6 metres.
  - (i) if the *storey* immediately below the uppermost *storey* is the first *storey*, which includes a front covered porch, the floor space of the front covered porch, measured to the outside edge of posts supporting the covered porch roof is added to the first *storey floor area* for this calculation;
  - (ii) if the *storey* immediately below the uppermost *storey* is the first *storey*, which includes an enclosed garage, the floor space of the enclosed garage is added to the first *storey floor area* for this calculation.
- (b) Sub-section (11)(a) does not apply:
  - (i) if in the case of a corner *lot*, there is a maximum of one *storey* of the *principal* building facing the narrowest *lot* line along the street; and
  - (ii) in all other cases, if there is a maximum of one *storey* of the *principal building* facing the street.
- (c) The maximum length of any wall of a detached building or structure for an accessory residential use and an accessory off-street parking use is 9.2 metres.

# (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

# (13) Other Regulations

- (a) Landscaping requirements for development in Northeast Coquitlam, under Part 5.
- (b) The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.

This page is intentionally left blank

# 1009 RS-9 Large Single Family Residential

### (1) Intent

This zone provides for the development of single family lots with a minimum *lot size* of 650 m<sup>2</sup>, with limited appropriate *accessory uses*.

# (2) Permitted Uses

*Principal uses*, limited to:

(a) One-family residential

*Accessory uses*, limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Accessory residential, as limited under Sub-section (9)(a)
- (d) Accessory home occupation, as limited under Section 508(3)

### (3) Conditions of Use

Not applicable for this zone.

### (4) Lot Size

- (a) A one-family residential use is not permitted on a lot having an area less than 650 m<sup>2</sup>.
- (b) The minimum *lot width* for a *one-family residential use* is 13.5 metres.
- (c) Notwithstanding Sub-section (4)(b), the minimum *lot width* for a *lot* with an *exterior lot corner* is 14.8 metres.

# (5) Density

- (a) The maximum density shall be 15 principal buildings per hectare.
- (b) The maximum *floor area* of the *principal building* on each *lot* is 505 m<sup>2</sup>, except that the *floor area* may be increased by up to 40 m<sup>2</sup> for an attached *accessory off-street parking use*.

# 1009 RS-9 Large Single Family Residential

# (6) Lot Coverage

All buildings and structures together must not exceed a lot coverage of 45%

### (7) Buildings Per Lot

No more than one *principal building* is permitted per *lot*.

### (8) Setbacks

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
One-family residential; and public parks	6.0	6.2	1.8	3.8
Accessory residential buildings and structures attached to or sited less than 1.6 metres from a building for residential use	6.0	6.2	1.8	3.8
Accessory off-street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	8.0 See Sub- section (9)(b)	6.2	1.8	3.8
Detached accessory residential and accessory off-street parking buildings and structures where sited 1.6 metres or more from a building for residential use	Not applicable. See Sub-sections (8)(e), (9)(a) and (9)(b)	1.2	1.2	3.8

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater.
- (c) The above setbacks are subject to increase under Sections 518 and 519 and 523 or decrease under Section 514.

### 1009 RS-9 Large Single Family Residential

- (d) Notwithstanding Section 514(2), covered porches are permitted to project by up to 1.7 metres into the front yard setback provided that:
  - (i) the porch shall have a usable floor space with dimensions that are no less than 1.5 metres by 3.0 metres;
  - (ii) the porch shall be unenclosed and protected by guard rails that comply with the British Columbia Building Code;
  - (iii) the porch is located at the basement or first storey; and
  - (iv) the porch is limited to a single *storey* in height, and its height does not exceed 4.0 metres, measured from the porch floor to the underside of the porch ceiling.
- (e) A minimum separation distance of 6.0 metres shall be maintained between the outermost projection of the rear face of the *principal building* and any detached accessory buildings or accessory off-street parking structures.

### (9) Locations of Uses

- (a) All detached accessory buildings shall be located in the rear yard.
- (b) Where a lane is provided all accessory off-street parking structures shall be located in the rear yard and access to accessory off-street parking spaces shall be from the lane.
- (c) The first *storey* of the *principal building* (including covered porches meeting the requirements under Sub-section (8)(d) and attached to the main front door entrance) must be:
  - (i) a minimum of 50% of the width of the buildings and structures facing the front lot line;
  - (ii) located at least 1.0 metre in front of any garage door(s); and
  - (iii) notwithstanding Sub-section (9)(c)(i), for a *lot* where the width of the *lot* at the *front lot line* is less than the minimum *lot width* as regulated under Sub-sections (4)(b) and (4)(c), Sub-section (9)(c)(i) will not apply.
- (d) No more than two accessory off-street parking spaces may be contained within the principal building.
- (e) Accessory off-street parking uses are not permitted within an exterior side lot line setback, except for unenclosed parking for a secondary suite, which must not be within 6 metres of the exterior lot corner.

### 1009 RS-9 Large Single Family Residential

#### (10) Height

- (a) Buildings and structures for one-family residential use must not exceed a height of:
  - (i) 7.3 metres, or
  - (ii) 11.0 metres for buildings and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.

### (11) Building Size

- (a) The exterior wall of the uppermost storey of the principal building must be set back from the main floor front exterior wall by a minimum of 0.6 metres.
  - (i) if the *storey* immediately below the uppermost *storey* is the first *storey*, which includes a front covered porch, the floor space of the front covered porch, measured to the outside edge of posts supporting the covered porch roof is added to the first *storey floor area* for this calculation;
  - (ii) if the *storey* immediately below the uppermost *storey* is the first *storey*, which includes an enclosed garage, the floor space of the enclosed garage is added to the first *storey floor area* for this calculation.
- (b) Sub-section (11)(a) does not apply:
  - (i) if in the case of a corner *lot*, there is a maximum of one *storey* of the *principal* building facing the narrowest *lot* line along the *street*; and
  - (ii) in all other cases, if there is a maximum of one *storey* of the *principal building* facing the street.
- (c) The maximum length of any wall of a detached building or structure for an accessory residential use and an accessory off-street parking use is 9.2 metres.

### (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

#### (13) Other Regulations

- (a) Landscaping requirements for development in Northeast Coquitlam, under Part 5.
- (b) The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.

# 1010 RS-10 Executive Single Family Residential

### (1) Intent

This zone provides for the development of single family lots with a minimum *lot size* of 650 m<sup>2</sup>, with limited appropriate *accessory uses*.

### (2) Permitted Uses

*Principal uses*, limited to:

(a) One-family residential

*Accessory uses*, limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Accessory residential, as limited under Sub-section (9)(a)
- (d) Accessory home occupation, as limited under Section 508(3)

### (3) Conditions of Use

Not applicable for this zone.

### (4) Lot Size

- (a) A one-family residential use is not permitted on a lot having an area less than 650 m<sup>2</sup>.
- (b) The minimum *lot width* for a *one-family residential use* is 18 metres.
- (c) Notwithstanding Sub-section (4)(b), the minimum *lot width* for a *one-family residential* use on a *lot* with an *exterior lot corner* is 20 metres.

#### (5) Density

- (a) The maximum density shall be 15 principal buildings per hectare.
- (b) The maximum floor area of the principal building on each lot is 505 m<sup>2</sup>, except that the floor area may be increased by up to 40 m<sup>2</sup> for an attached accessory off-street parking use.

# 1010 RS-10 Executive Single Family Residential

# (6) Lot Coverage

All buildings and *structures* together must not exceed a lot coverage of 45%.

### (7) Buildings Per Lot

No more than one *principal building* is permitted per *lot*.

#### (8) Setbacks

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
One-family residential; and public parks	7.6	6.2	1.8	3.8
Accessory residential buildings and structures attached to or sited less than 1.6 metres from a building for residential use	7.6	6.2	1.8	3.8
Accessory off-street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	9.6 See Sub- Section (9)(b)	6.2	1.8	3.8
Detached accessory residential and accessory off-street parking buildings and structures where sited 1.6 metres or more from a building for residential use	Not applicable. See Sub-sections (8)(e), (9)(a) and (9)(b)	6.2	1.8	3.8

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater.
- (c) The above setbacks may increase under Sections 518, 519 and 523 or decrease under Section 514.

# 1010 RS-10 Executive Single Family Residential

- (d) Notwithstanding Section 514(2), covered porches are permitted to project into the front yard setback by up to 1.7 metres provided that:
  - (i) the porch shall have a usable floor space with dimensions that are no less than 1.5 metres by 3.0 metres;
  - (ii) the porch shall be unenclosed and protected by guard rails that comply with the British Columbia Building Code;
  - (iii) the porch is located at the basement or first storey; and
  - (iv) the porch is limited to a single *storey* in height, and its height does not exceed 4.0 m, measured from the porch floor to the underside of the porch ceiling;
- (e) A minimum separation distance of 6.0 metres shall be maintained between the outermost projection of the rear face of the *principal building* and any detached *accessory buildings* or *accessory off-street parking structures*.

### (9) Locations of Uses

- (a) All detached accessory buildings shall be located in the rear yard.
- (b) Where a lane is provided all accessory off-street parking structures shall be located in the rear yard and access to accessory off-street parking spaces shall be from the lane.
- (c) The first *storey* of the *principal building* (including covered porches meeting the requirements under Sub-section (8)(d) and attached to the main front door entrance) must be:
  - (i) a minimum of 50% of the width of the *buildings* and *structures* facing the *front lot line*; and
  - (ii) located at least 1.0 metre in front of any garage door(s);
  - (iii) notwithstanding Sub-section (9)(c)(ii), for a dwelling where all the garage doors face the *interior side lot line*, Sub-section (9)(c)(ii) will not apply; and
  - (iv) notwithstanding Sub-section (9)(c)(i), for a *lot* where the width of the *lot* at the *front lot line* is less than the minimum *lot width* as regulated under Sub-sections (4)(b) and (4)(c), Sub-section (9)(c)(i) will not apply.
- (d) No more than three *accessory off-street parking* spaces may be contained within the *principal building*.
- (e) Accessory off-street parking uses are not permitted within an exterior side lot line setback, except for unenclosed parking for a secondary suite, which must not be within 6 metres of the exterior lot corner.

### 1010 RS-10 Executive Single Family Residential

### (10) Height

- (a) Buildings and structures for one-family residential use must not exceed a height of:
  - (i) 7.3 metres; or
  - (ii) 11.0 metres for buildings and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.

### (11) Building Size

- (a) The exterior wall of the uppermost storey of the principal building must be set back from the main floor front exterior wall by a minimum of 0.6 metres.
  - (i) if the *storey* immediately below the uppermost *storey* is the first *storey*, which includes a front covered porch, the floor space of the front covered porch, measured to the outside edge of posts supporting the covered porch roof is added to the first *storey floor area* for this calculation;
  - (ii) if the *storey* immediately below the uppermost *storey* is the first *storey*, which includes an enclosed garage, the floor space of the enclosed garage is added to the first *storey floor area* for this calculation.
- (b) Sub-section (11)(a) does not apply:
  - (i) if in the case of a corner *lot*, there is a maximum of one *storey* of the *principal* building facing the narrowest *lot* line along the *street*; and
  - (ii) in all other cases, if there is a maximum of one *storey* of the *principal building* facing the street.
- (c) The maximum length of any wall of a detached building or structure for an accessory residential use and an accessory off-street parking use is 9.2 metres.

### (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

### (13) Other Regulations

(a) Landscaping requirements for development in Northeast Coquitlam, under Part 5. The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.

# 1011 RS-11 Estate Single Family Residential

### (1) Intent

This zone provides for the development of single family lots with a minimum *lot size* of 1000 m<sup>2</sup>, with limited appropriate *accessory uses*.

### (2) Permitted Uses

*Principal uses*, limited to:

(a) One-family residential

Accessory uses, limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Secondary Suite, as limited under Section 508(2)
- (c) Accessory residential, as limited under Sub-section (9)(a)
- (d) Accessory home occupation, as limited under Section 508(3)

### (3) Conditions of Use

Not applicable for this zone.

#### (4) Lot Size

- (a) A one-family residential use is not permitted on a lot having an area less than 1000 m<sup>2</sup>.
- (b) The minimum *lot width* for a *one-family residential use* is 24 metres.

### (5) Density

- (a) The maximum *density* shall be 10 *principal buildings* per hectare.
- (b) The maximum floor area of the principal building on each lot is 755 m<sup>2</sup>, except that the floor area may be increased by up to 40 m<sup>2</sup> for an attached accessory off-street parking use.

### (6) Lot Coverage

All buildings and structures together must not exceed a lot coverage of 40%.

# 1011 RS-11 Estate Single Family Residential

# (7) Buildings Per Lot

No more than one *principal building* is permitted per *lot*.

### (8) Setbacks

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
One-family residential; and public parks	10.0	7.6	1.8	3.8
Accessory residential buildings and structures attached to or sited less than 1.6 metres from a building for residential use	10.0	7.6	1.8	3.8
Accessory off-street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	12.0 See Sub- Section (9)(b)	7.6	1.8	3.8
Detached accessory residential and accessory off-street parking buildings and structures where sited 1.6 metres or more from a building for residential use	Not applicable. See Sub- sections (8)(e), (9)(a) and (9)(b)	1.2	1.2	3.8

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater.
- (c) The above setbacks may increase under Sections 518, 519 and 523 or decrease under Section 514.
- (d) Notwithstanding Section 514(2), covered porches are permitted to project into the front yard setback by up to 1.7 metres provided that:
  - (i) the porch shall have a usable floor space with dimensions that are no less than 1.5 metres by 3.0 metres;

### 1011 RS-11 Estate Single Family Residential

- (ii) the porch shall be unenclosed and protected by guard rails that comply with the British Columbia Building Code;
- (iii) the porch is located at the basement or first *storey*; and attached to the main front door entrance of the residence; and
- (iv) the porch is limited to a single *storey* in height, and its height does not exceed 4.0 m, measured from the porch floor to the underside of the porch ceiling.
- (e) A minimum separation distance of 6.0 metres shall be maintained between the outermost projection of the rear face of the *principal building* and any detached *accessory buildings* or *accessory off-street parking structures*.

### (9) Locations of Uses

- (a) All detached accessory buildings shall be located in the rear yard.
- (b) Where a lane is provided all accessory off-street parking structures shall be located in the rear yard and access to accessory off-street parking spaces shall be from the lane.
- (c) The first *storey* of the *principal building* (including covered porches meeting the requirements under Sub-section (8)(d) and attached to the main front door entrance) must be:
  - (i) a minimum of 50% of the width of the buildings and structures facing the front lot line; and
  - (ii) located at least 1.0 metre in front of any garage door(s);
  - (iii) notwithstanding Sub-section (9)(c)(ii), for a dwelling where all the garage doors face the *interior side lot line*, Sub-section (9)(c)(ii) will not apply; and
  - (iv) notwithstanding Sub-section (9)(c)(i), for a *lot* where the width of the *lot* at the *front lot line* is less than the minimum *lot width* as regulated under Sub-section (4)(b), Sub-section (9)(c)(i) will not apply.
- (d) No more than three *accessory off-street parking* spaces may be contained within the *principal building*.
- (e) Accessory off-street parking uses are not permitted within an exterior side lot line setback, except for unenclosed parking for a secondary suite, which must not be within 6 metres of the exterior lot corner.

#### (10) Height

- (a) Buildings and structures for one-family residential use must not exceed a height of:
  - (i) 7.3 metres; or
  - (ii) 11.0 metres for buildings and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.

# 1011 RS-11 Estate Single Family Residential

- (b) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.

### (11) Building Size

- (a) The exterior wall of the uppermost storey of the principal building must be set back from the main floor front exterior wall by a minimum of 0.6 metres.
  - (i) if the *storey* immediately below the uppermost *storey* is the first *storey*, which includes a front covered porch, the floor space of the front covered porch, measured to the outside edge of posts supporting the covered porch roof is added to the first *storey floor area* for this calculation;
  - (ii) if the *storey* immediately below the uppermost *storey* is the first *storey*, which includes an enclosed garage, the floor space of the enclosed garage is added to the first *storey floor area* for this calculation.
- (b) Sub-section (11)(a) does not apply:
  - (i) if in the case of a corner *lot*, there is a maximum of one *storey* of the *principal* building facing the narrowest *lot* line along the *street*; and
  - (ii) in all other cases, if there is a maximum of one *storey* of the *principal building* facing the street.
- (c) The maximum length of any wall of a detached building or structure for an accessory residential use and an accessory off-street parking use is 9.2 metres.

#### (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

### (13) Other Regulations

- (a) Landscaping requirements for development in Northeast Coquitlam, under Part 5.
- (b) The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.

### 1012 RTM-1 Street-Oriented Village Home Residential

### (1) Intent

This zone provides for the development of street-oriented multiple-unit residential development with a minimum *lot size* of 210 m<sup>2</sup>, with limited appropriate *accessory uses*.

### (2) Permitted Uses

*Principal uses*, limited to:

(a) Street-Oriented Village Home Residential, as limited under Sub-section (3)(a)

Accessory uses, limited to:

- (a) Boarding, as limited under Section 508(1)
- (b) Accessory residential, as limited under Sub-section (9)(a)
- (c) Accessory home occupation, as limited under Section 508(3)

# (3) Conditions of Use

- (a) A street-oriented village home residential use is permitted only where it complies with all of the following:
  - (i) no more than eight principal buildings are attached; and
  - (ii) areas of a *lot* that are used for *accessory off-street parking* purposes including *buildings*, *structures*, parking pads and driveways shall be accessed from a *lane*.

### (4) Lot Size

- (a) A street-oriented village home residential use is not permitted on a fee-simple lot having an area less than 210 m<sup>2</sup>.
- (b) The minimum width of a *principal building* is 4.5 metres.

# (5) Density

- (a) The maximum *floor area ratio* for all *principal buildings* on a *lot* shall be 0.9.
- (b) The maximum *density* shall be 48 *principal buildings* per hectare; except that in the case of special needs and/or affordable housing on a site or sites owned by the *City* of Coquitlam and/or a registered non-profit agency the maximum *density* shall be 89 *dwelling units* per hectare.

### (6) Lot Coverage

All buildings and structures together must not exceed a lot coverage of 45%.

# (7) Buildings Per Lot

- (a) No more than one principal building is permitted per lot.
- (b) Where a fee-simple *lot* is stratified, Sub-section (7)(a) does not apply.

#### (8) Setbacks

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
Street-Oriented Village Home Residential and public parks	4.0	6.2	0.0 where the interior side wall of the street-oriented village home residence adjoins the interior side wall of a neighbouring street-oriented village home; otherwise 1.4	3.0
Accessory residential and accessory off-street parking buildings and structures attached to or sited less than 1.6 metres from a building for residential use	4.0	6.2	0.0 where the interior side wall of the street-oriented village home residence adjoins the interior side wall of a neighbouring street-oriented village home; otherwise 1.4.	3.8

Use	Front Lot Line (metres)	Rear Lot Line (metres)	Interior Side Lot Line (metres)	Exterior Side Lot Line (metres)
Detached accessory residential buildings and structures where sited 1.6 metres or more from a building for residential use	Not applicable. See Sub- sections (8)(f) and (9)(a)	6.2	1.2	3.8
Detached accessory off- street parking buildings and structures where sited 1.6 metres or more from a building for residential use	Not applicable. See Sub- sections (8)(f), (9)(a) and (9)(b)	1.2	0.0	3.8

- (b) The siting distance is measured from the outermost limit of the *building* or any permitted projections, whichever is greater.
- (c) A minimum of 50% of the width of the first *storey* of the *principal building* (including porches) facing the *front lot line* must be sited within 1.0 metre of the front setback described in Sub-section (8)(a).
- (d) The above setbacks may increase under Sections 518, 519 and 523 or decrease under Section 514.
- (e) Notwithstanding Section 514(2), covered porches are permitted to project into the front yard setback by up to 1.7 metres provided that:
  - (i) the porch shall have a usable floor space with dimensions that are no less than 1.5 metres by 3.0 metres;
  - (ii) the porch shall be open on at least two sides or protected by guard rails that comply with the British Columbia Building Code;
  - (iii) the porch is located at the basement or first storey; and
  - (iv) the porch is limited to a single *storey* in height, and its height does not exceed 4.0 m, measured from the porch floor to the underside of the porch ceiling;
- (f) A minimum distance of 6.0 metres shall be maintained between the outermost projection of the rear face of the *principal building* and any detached *accessory buildings* or *accessory off-street parking structures*.

- (g) Notwithstanding Section 514(1) chimneys, pilasters, bay windows, heating or ventilating equipment, or ornamental features are not permitted to project into the *interior side lot line* setbacks described under Sub-section 8(a), for the first *storey* of any *building* or *structure*.
- (h) The interior side lot line setback of a detached garage may be reduced to:
  - (i) 0.0 m provided that the full length of the interior side *wall* of the garage is adjoined to the full length of the interior side *wall* of the garage on a neighbouring parcel that is also used for *street-oriented village home residential* purposes; and
  - (ii) 0.9 m in the case of a *lot* with an *exterior lot corner*.

### (9) Location of Uses

- (a) All detached accessory buildings shall be located in the rear yard.
- (b) All accessory off-street parking structures shall be located in the rear yard and access to accessory off-street parking spaces shall be from the lane.
- (c) Accessory off-street parking uses are not permitted within an exterior side lot line setback.

## (10) Height

- (a) Buildings and structures for street-oriented village home residential use must not exceed a height of:
  - (i) 7.3 metres; or
  - (ii) 11.0 metres for buildings and *structures* having a roof slope with a pitch of 3 in 12 or greater for an area of at least 80% of all roof surfaces.
- (b) Detached buildings and structures for accessory residential or accessory off-street parking must not exceed a height, measured from finished grade, of:
  - (i) 3.7 metres; or
  - (ii) 4.6 metres, for an *accessory building* that has a roof with a pitch of 4 in 12 or greater for an area of at least 80% of all roof surfaces.

### (11) Building Size

The maximum length of any wall of a detached building for an accessory off-street parking use is 7.0 m.

#### (12) Off-Street Parking and Loading

The regulations under Part 7 apply.

# (13) Other Regulations

- (a) Landscaping requirements for development in Northeast Coquitlam, under Part 5.
- (b) An in-ground swimming pool is not permitted on any portion of a lot in the RTM-1 Street-Oriented Village Home Residential zone.
- (c) The regulations under Part 2, Part 3, Part 4, Part 5, and Part 6 apply.